

Haymaker OP-115, Vari Turning and raking of fodder and cuttings



Mowing technology Forage harvesting

Mulching technology Tillage Cleaning Winter service Transport Special applications



Rapid

Haymaker OP-115, Vari Overview of types and compatibility

Mark-Behind Lactor Model Mondo M09 Mondo M14 Varea M141 Varea M141 Varea M161 Varea M161	VAREA (ORBITO
Attachment name Art. no.	
Haymaker OP-115, Vari 1395 - <td></td>	
Optional extras	
Ballast weight 8.5 kg • -	

Main areas of application



Multiple Applications with the haymaker are often run as an application following previous work steps

with the single-axle walk-behind tractor. Here, the tool-free changing system and the use of the same walk-behind tractor are proven in the areas of application.

The main areas of application are:

- Landscape maintenance
- Green space maintenance
- Green/paved area maintenance

Lightweight and manoeuvrable unit combination

This haymaker is operated on the Rapid Rex and is characterised by its low dead weight, compactness and manoeuvrability.

The subsequent step after mowing to raking windrow cuttings on meadows, flower strips, etc. represents an application. On small embankments, for example along water channels or at water retention basins, the cuttings can be transported upwards by a working width for subsequent removal.

Versatile mowing specialist

If this haymaker is attached to the specialised Rapid Rex mountain mower, the process chain can be extended beyond mowing and landscape maintenance can be carried out, e.g. when the removal of the cuttings is required.

In addition to these attachments for mowing and the recovery of cuttings, other attachments such as the Eco-mulcher, sweeper brush, snowplough, etc. can be attached and the machine combinations can thus be used and utilised all year round – an interesting unit also outside the mountain agriculture.



