## Rapid

### **Round baler**

Collect, compress, press and bind cuttings and crops



Mowing technology

Forage harvesting

Mulching technology

Tillage

Cleaning

Winter service

Transport

Special applications





### **Round baler**

# Overview of types and compatibility

WALK	-BEHIND TRACTOR MODEL		REX	MONDO M091	MONDO M141	KIPOS M141	URI E041	SWISS	MONTA M141	MONTA S141	MONTA M161	MONTA S161	MONTA M231	MONTA S231	VAREA M141	VAREA S141	VAREA M161	VAREA S161	VAREA M231	VAREA S231	ORBITO
	Attachment name	Art. no.																			
	Round baler, CAEB	6925	-	-	-	-	-	-	-	-	•	•	•	•	-	-	•	•	•	•	•
	Optional extras																				
	Dual tyres	6355	-	-	-	-	-	-	-	-	•	•	•	•	-	-	•	•	•	•	•
	Star rake	6356	-	-	-	-	-	-	-	-	•	•	•	•	-	-	•	•	•	•	•
	Roll of netting	6131	-	-	-	-	-	-	-	-	•	•	•	•	-	-	•	•	•	•	•
	External dead man system, cpl.	269718	-	-	-	-	-	-	-	-	•	-	•	-	•	-	•	-	•	-	-
	Round baler control	269721	-	-	-	-	-	-	-	-	-	•	-	•	-	•	-	•	-	•	•

#### Main areas of application



Multiple Applications with the round baler are often run as an application following previous work

steps with the single-axle walk-behind tractor. Here, the tool-free changing system and the use of the same walkbehind tractor are proven in the areas of application:

- Mountain agriculture
- Agriculture
- Landscape maintenance
- Green/paved area maintenance

#### Press handy round baler

Dried fodder, other cuttings and crops or leaves, etc. have a large volume that requires a lot of space and effort for both transport and storage.

By compressing, pressing and binding round bales, the volume is reduced and a transportable and storable unit is created.

This work step changes and optimises procedures and process chains, for example in grassland management or landscape maintenance.

### **Collecting and pressing**

The pickup of the round baler is used primarily to pick up dry fodder deposited in the swath, but also other cuttings and crops or leaves, etc., and feed it into the press chamber. A round ball is formed by the rotating movement.

After the winding process, the round bale, which weighs approx. 20 kg depending on the cuttings, is wrapped with a net and can be removed after opening the press chamber.



