

# Rapid

## Mini Cargo

Versatile transport unit with tilting mechanism



Mowing technology

Forage harvesting

Mulching technology

Tillage

Cleaning

Winter service

Transport

Special applications



## Overview of types and compatibility

WALK-BEHIND TRACTOR MODEL			REX	MONDO M091	MONDO M141	KIPOS M141	URI E041	SWISS	MONTA M141	MONTA S141	MONTA M161	MONTA S161	MONTA M231	MONTA S231	VAREA M142	VAREA S142	VAREA M162	VAREA S162	VAREA M231	VAREA S231	ORBITO	
<b>Attachment name</b>		<b>Art. no.</b>																				
Mini Cargo, CAEB payload 250 kg		1441	-	•	•	•	•	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Mini Cargo, CAEB payload 400 kg		8894	-	-	-	-	-	-	•	•	•	•	•	•	•	•	•	•	•	•	•	-
<b>Optional extras</b>																						
Dead man system (model up to 2013)		259074	-	•	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Dead man system		260581	-	•	•	•	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Dead man system		272175	-	-	-	-	•	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

### Main areas of application



Work assignments with the Mini Cargo are usually secondary applications. Here, the tool-free changing system and the use of the same walk-behind tractor are proven in the areas of application:

- Horticulture and landscape gardening
- Vegetable gardening
- Fruit-growing
- Agriculture
- Green/paved area maintenance

### Transport of various goods and materials

The attachment consists of frame, chassis and tilting bucket. The bucket can be filled and loaded with all materials and goods. Thanks to the tilting mechanism, bulk material can be easily and conveniently unloaded to the front.

The narrow design allows easy access to narrow entrance doors and narrow access roads.

### Chassis and wheels

The chassis on the attachment frame is equipped with swivel castor wheels on the actively steered machines and connection flanges 78/80 mm.

A steering mechanism is installed for the non-actively steered machines and connection flanges 52/54 mm. The wheels of the attachment are controlled by a separate handlebar.

